


**Engineered Handling Solutions Since 1869** 





## Stainless Steel Strap Hoists

These clean room hoists meet the processing needs of pharmaceutical processors and hightech manufacturers. David Round strap hoists are designed for operation inside controlled environments. Various models and trolley options accommodate loads up to 4,000 pounds.

## **Lube-Free Lifting Strap**

The lubrication-free, urethane-coated lifting strap eliminates contamination potential associated with chain or wire rope hoists: no metal-on-metal abrasion to create particulate.

## **Crack & Crevice Free Construction**

The easy-to-clean open design of David Round strap hoists features stainless steel surfaces polished in addition to flush mounting faces, ground welds and plugged fasteners to reduce the likelihood of contamination build-up.



Stainless Steel Strap Hoists

Capacities up to 2 metric tons.
Lift heights, beam sizes and
voltages are all built to order to
your application's requirements.



- Polished stainless steel external components
- Fully sealed stainless steel gearing with food-grade bath lubrication
- Clean room grade stainless steel motor and motor brake
- Lubrication-free urethane-coated lifting strap
- Stainless steel load hook with latch
- Stainless steel NEMA 4X electrical enclosure
- Single speed reversing contactor with thermal overload relay and transformer
- Upper limit switches (paddle style)
- NEMA 4X 2-button plastic pendant
- Lug mounted

## **Options**

- Hook travel limit switch
- Various levels of polished surfaces
- Variable speed operation with AC inverter
- Stainless steel trolleys available, manual or powered
- Nylon / composite trolley wheels
- Trolley soft start
- Mainline contactor
- Complete overhead systems
- Rotary limit switches



Hybrid hoists offer an economical alternative for some applications (Stainless steel with some painted components.)



Engineered Handling Solutions Since 1869

10200 Wellman Road, Streetsboro, OH 44241 Phone: 1-800-535-2725 or (330) 656-1600

Fax: (330) 656-1601

Email: info@davidround.com www.davidround.com